

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 61114930 A

(43) Date of publication of application: 02.06.1986

(51) Int. Cl B65G 67/02

B60P 1/00

(21) Application number: 59238040

(22) Date of filing: 12.11.1984

(71) Applicant: MURATA MACH LTD

(72) Inventor: SHIOMI TADATAKA

MITANI KEIO

YASUDA YUKINOBU

(54) LOCKING DEVICE FOR TRUCK  
LOAD-CARRYING PLATFORM

10 locked by the cylinder 14, the load-carrying platform 6a will not be depressed.

(57) Abstract:

COPYRIGHT: (C)1986,JPO&Japio

PURPOSE: To prevent variation of the load-carrying surface on transferring of a load onto a truck by abutting an abutting member on the ground side against the bottom surface of an auxiliary bumper on the truck side and locking the same.

CONSTITUTION: When a truck 6 is moved backwardly, a roller 7 on the ground side goes ahead along a tilting surface 9b of an auxiliary bumper 9 and then the bottom surface 9a and is stopped, when the auxiliary bumper 9 comes in abutment against a positioning stopper 22. Then, a directional control valve of a fluid cylinder 14 is switched by the display of a proximity sensor 14 to lock a piston rod 15 of the cylinder 14. When a load on a traverser is transferred onto the truck 6, the load applied to a load-carrying platform is increased, but as the bottom surface 9a of the auxiliary bumper on the undersurface of the load carrying platform is kept in abutment against the roller 7 of a lever

